

EPSON®
EXCEED YOUR VISION



SurePress® | Digital Label Press

Epson's SurePress digital label press — an innovative choice for short-run print jobs.

Epson's SurePress L-4033A and L-4033AW have all the tools you need to enter the world of digital label printing. You'll achieve impressive, professional results, while handling short-run jobs quickly and efficiently. So boost your bottom line by offering a wider range of printing solutions to your customer base, plus just-in-time production to meet tight schedules. It's never been easier to go digital.

Produce high-quality labels — cutting-edge MicroPiezo® inkjet technology provides ultra precise drop formation and placement to deliver smooth gradations, remarkable color quality, and sharp detail for easy bar code readability, plus crisp small type and line work. Epson's SurePress L-4033AW AQ ink set includes White ink for solid, opaque white printing on materials such as clear film and metallic substrates.


Seven-color, industrial-quality ink set — including Orange, Green and White for clear film and metallic substrates to produce a remarkable range of colors



Epson's acclaimed MicroPiezo multi-print-head technology — delivers well-defined dots for accurate, consistent printing



Variable-sized Droplet Technology — ensures smooth gradations and accurate colors for optimum image quality



Transfer short-run jobs to SurePress for greater flexibility and efficiency.

You'll be amazed at how flexible your operation will become with Epson's SurePress. Make-ready time is dramatically reduced and substrate changeover is quick and efficient. Operation is simple and maintenance requirements are minimal, which means you'll easily increase productivity and profitability.

Boost profitability — ensures lower make-ready costs while offering a wider range of printing solutions

Get versatile media support — print on a wide range of standard substrates up to 12.6 mil thick and rolls from 3.15 to 13 inches wide


Reduce waste — no chemicals or plates required in the pre-press process, plus less media and ink used when setting up short-run jobs

Enhance productivity — transfer time-consuming short-run jobs to the SurePress for more cost-efficient and timely results


Easily operate — the intuitive touch-screen panel makes digital printing simple



Touch-screen panel makes operation easy



No pre-coated media required — two-stage drying process ensures optimum ink adhesion



SurePress | Digital Label Press

Specifications†

Printing Technology	EPSON MicroPiezo inkjet technology	
Resolution	720 x 720 dpi (for paper), 1440 x 720 dpi (for film)	
Ink Type	EPSON industrial-quality, water-based, resin-coated, pigment ink system (SurePress AQ)	
Ink Colors	Cyan, Magenta, Yellow, Black, Green, Orange, White (L-4033AW)	
Cartridge Fluids	Over print, Moisture liquid	
Web Width	3.15" – 13" (80 – 330 mm) Adjustable to support any width in this range	
Image Size	36" x 12.4" (914.4 x 315.2 mm) maximum repeat lengths	
Print Speed	Up to 16 feet (5 m) per minute at 720 x 720 dpi (on paper)	
Substrate Support	Standard self-adhesive label stock and film (no pre-coating required) Semi-gloss, gloss and matte paper stock, BOPP, PET, Yupo, clear and metallic films	
Substrate Thickness	0.004"– 0.013" (0.10 – 0.32 mm) or 100 – 320 microns (4 – 12.6 mil)	
Unwinder / Rewinder Capacity (maximum)	220 lb (100 kg) / 23.6" (600 mm) diameter / 3280.8 feet (1000 m) maximum length with 3" (76 mm) inner core	
Press Dimensions (W x D x H)	12.43' x 6.06' x 6.00' (3788 x 1847 x 1828 mm)	
Rewinder Dimensions (W x D x H)	4.30' x 2.95' x 3.28' (1310 x 900 x 1000 mm)	
Weight of Press	Approximately 4078 lb (1850 kg) including rewinder	
Weight of Rewinder	Approximately 397 lb (180 kg)	
Network Connectivity	Ethernet 1000 Base-T or higher is recommended	
Temperature (operating)	64 ° to 82 °F (18 ° to 28 °C)	
Relative Humidity (operating)	35 – 55% (no condensation)	
Power Requirements	Rated voltage — AC (three-phase system) 200 V Input voltage range — rated ± 10% (180–220 V) Rated frequency — 50 – 60 Hz	Input frequency range — rated ± 1% Rated current — 30 A
Maximum Sound Level (operating)	75 dB or less (excluding the alarm sound)	

Dimensions



Epson America, Inc. | 3840 Kilroy Airport Way, Long Beach, CA 90806 | www.epson.com

† Specifications and terms are subject to change without notice

EPSON, MicroPiezo and SurePress are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2012 Epson America, Inc. CPD-32247R3 8/12

For more information, please visit www.epson.com/surepress

Better Products for a Better Future™

For more information on Epson's environmental programs, go to eco.epson.com